

CCAM3USB2.0

Ultra Miniature 1/3" USB2.0 Color CCD Cameras

- 1/3" 410,000 Pixels WDR CMOS Sensor
- High sensitivity 0.5lux at F1.2
- Dynamic Range : 95dB typical
- Vscanning System : NTSC/PAL selection
- White Balance Mode : ATW/AWC/Manual
- Text display : 24 alphanumeric characters
- On-screen Menu & Adjustment



■ SPECIFICATIONS

| ITEMS | SPECIFICATIONS |
|--------------------------|--|
| Pick-up Device | 1/3-Inch WDR CMOS Device |
| Effective Pixels (H)x(V) | 720×540 |
| TV System | NTSC/PAL selectable |
| Sync System | Internal |
| Horizontal Resolution | 480 TV lines |
| Video Outputs | Composite Video (1.0Vp-p / 75Ω) |
| Video S/N Ratio | 50 dB (AGC Off) |
| Minimum Illumination | 0.5 lux (F1.2, Contrast On) |
| AGC Mode | 4~26dB selectable |
| White Balance | ATW / AWC / Manual |
| Backlight Compensation | Auto (Center Window) |
| Auto Electronic Shutter | On / Off selectable |
| Auto Iris Lens | VIDEO/DC selectable |
| Gamma Correction | Variable |
| Text Display | 24 Alphanumeric Characters |
| PC Interface | USB2.0 |
| Lens Mount | C /CS Mount |
| Power | DC 12V |
| Operating temperature | -10□ to 50□ (14□ to 122□) |
| Weight | 140g (0.31 lbs) |
| Dimensions(with lens) | 41(W)×41(H)×73(D)mm [1.6(W)×1.6(H)×2.8(D)inch] |