



1/3" 1.4/2.3mm		
FOCAL LENGTH		f=2.3mm
MAX. DIAMETER (RATIO)		F=1:1.4~16~CLOSE
ELEMENT		7-GROUP 8ELEMENTS
PICTURE SIZE		3.6x4.8mm
ANGLE	VER. ANGLE	87.4 °
	HOR. ANGLE	116.1 °
	DIA. ANGLE	143.2 °
DISTORTION (TV)		-21.9%
SHOOTING RANGE AT MINIMUM FOCUS DISTANCE	VER.	398mm
	HOR.	665mm
	DIA.	1237m
MINIMUM FOCUS DISTANCE		0.2m
FLANGE BACK		12.5mm in air
BACK FOCUS		8.30mm in air
FILTER SCREW SIZE		—
FRONT/REAR EFFECTIVE DIA.		φ 23.4mm φ 8.7mm
MOUNT		CS-MOUNT
EXIT PUPIL		256.4mm
TEMPERATURE RANGE		-10~45 °C
STORAGE TEMPERATURE RANGE		-40~60 °C
RESOLUTION CENTER/CORNER		100 LP/mm 40 LP/mm
STOPPER STRENGTH		10kgf/cm
ENDURANCE TESTS		5,000Times 5,000Times
OPERATING TORQUE IRIS/FOCUS		50~600gf/cm 100~1000gf/cm
WEIGHT		66g

品名 1/3" F1.4/2.3mm
部番 LM2.3PBR