



0.1m 線出し量:0.84

| 1/3" F1.8/9mm | | |
|---------------------------|------------|----------------------------------|
| FOCAL LENGTH | | f=9mm |
| MAX. DIAMETER (RATIO) | | F=1:1.8~11 |
| PICTURE SIZE | | 3.6x4.8mm |
| ANGLE | VER. ANGLE | 22.8° |
| | HOR. ANGLE | 30.2° |
| | DIA. ANGLE | 37.6° |
| DISTORTION (TV) | | -0.6% |
| SHOOTING RANGE AT | VER. | 43mm |
| MINIMUM FOCUS | HOR. | 58mm |
| DISTANCE | DIA. | 73mm |
| MINIMUM FOCUS DISTANCE | | 0.1m |
| FLANGE BACK | | 12mm in air |
| BACK FOCUS | | 8.64mm in air |
| FILTER SCREW SIZE | | --- |
| FRONT/REAR EFFECTIVE DIA. | | F. ϕ 11.8mm R. ϕ 8.3mm |
| MOUNT | | NF-MOUNT (M17x0.75) |
| EXIT PUPIL | | -23.5mm |
| TEMPERATURE RANGE | | -10~+50°C |
| STORNG TEMPERATURE RANGE | | -20~+60°C |
| WEIGHT | | 40g |

| | | | | | | | |
|----------|-------|-----|---------------|----|----|---|----|
| | | 尺度 | 1/1 | 承認 | 八木 | 製 | 富永 |
| | | 機種名 | S10-241 | | | | |
| | | 機種番 | 1/3" F1.8/9mm | | | | |
| 10.08.09 | 作成年月日 | | | | | | |