
# Machine Vision

**AZURE Lenses Series** 





#### **COMPANY PROFILE**



AZURE Photonics Co., Ltd, is an ISO 9001:2015 certified leading worldwide manufacturer of customized optical components and optical assemblies.

With an innovative facility based in Fuzhou (China) since 2000 and global sales distribution and support at key global locations, AZURE utilizes advanced fabrication equipments and state of the art testing instrumentation and methods to turn concepts and prototypes into high quality cost effective solutions scaled up to serial production. Our experienced team of technical experts also offer optical and mechanical design services for the assemblies from the very beginning your project starts.

We produce a wide range of off-the-shelf and custom objective lenses working with area scan cameras/ line scan cameras as well as OEM optics – lenses(spherical, cylindrical), mirrors, windows, filters, prisms and beamsplitters. Our products are widely used in factory automation, logistics automation, motion capture systems, ITS(intelligent TransportSystem), life science, biometrics and other high-tech industries.

AZURE is committed to deliver customers with Quality Products, On-time Delivery, competitive pricing and 100% CustomerSatisfaction.

# **DIRECTORY**

2MP Lenses Series	3	UV Lenses Series	27
3MP Lenses Series	5	SWIR Lenses Series	28
5MP Lenses Series	7	Telecentric Lenses Series	30
6MP Lenses Series	9	Board Lenses Series	35
10MP Compact Lenses Series	11	The Near/Far Field Lenses Series	41
Large Format Lenses Series	13	Lenses Accessories	44
Manual Zoom Lenses Series	15	Endoscope	45
Macro Zoom Lenses Series	16	Filter Series	46
F/T-mount Lenses Series	17		
V-mount Lenses Series	20		





Item No		AZURE-0420MM	AZURE-0614MM	AZURE-0814MM
Resolution		100lp/mm (2MP)	100lp/mm (2MP)	100lp/mm (2MP)
Format		1/2*	1/2"	1/2*
Mount		C	c	C
Focal Length		4mm	6mm	8mm
F/Na		F2.0~F16	F1.4~F16	F1.4~F16
Back Focus		8.77mm	9.26mm	11.02mm
Iris Type	-	M-Iris	M-Iris	M-Iris
- W / P - W	1/2"Format	90°× 61.8°×77.4°	67°× 43.8°×56.6°	54°× 33.6°×43.8°
Angle of view	1/3"Format	73.74°× 48.46°×61.93°	53.13°× 33.39°×43.6°	41.11°× 25.36°×33.4°
(DXVXH)	1/4°Format	53.13°× 33.4°×43.6°	36.87°× 22.6°×29.86°	28.07° × 17.06° × 25.36°
Distortion		<-2.8%	<-1%	<-1%
Working Dista	nce	0.1m ~ ∞	0.1m~∞	0.1m~ ∞
Design Wavele	ength	400~700nm	400~700nm	400~700nm
Filter Thread		No	M30.5 × 0.5	M30.5 × 0.5
Dimension		¢ 44.5 × 35.97mm	¢ 32.5 × 32.51mm	¢32.5 × 38.5mm
Weight		130g	100g	107g



Item N	lo	AZURE-1214MM	AZURE-1614MM
Resolution		100lp/mm (2MP)	100lp/mm (2MP)
Format		2/3"	2/3"
Mount		C	C
Focal Length		12mm	16mm
F/No		F1.4~F16	F1.4~F16
Back Focus		9.83mm	9.87mm
Iris Type		M-Iris	M-Iris
	2/3*Format	48.86°× 30.44°×39.94°	36°× 22.02°×29.12°
Angle of view ( DXVXH )	1/2*Format	36.86°× 22.62°×29.86°	28.07°× 17.06°×22.62°
(DYAVU)	1/3"Format	28.07°× 17.06°×22.62°	21.23°× 12.84°×17.06°
	1/4°Format	18.92°× 11.42°×15.19°	14.25°× 8.58°×11.42°
Distortion		<-1%	<-1%
Working Dista	nce	0.1m~ ∞	0.1m~∞
Design Wavele	ength	400~700nm	400~700nm
Filter Thread		M30.5 × 0.5	M30.5 × 0.5
Dimension		¢ 32,5 × 41,62mm	¢ 32.5 × 35.24mm
Weight		85g	80g



Item N	lo.	AZURE-2514MM	AZURE-3514MM
Resolution		100lp/mm (2MP)	100lp/mm (2MP)
Format		2/3"	2/3"
Mount		С	С
Focal Length		25mm	35mm
F/No		F1.4~F32	F1.4~F32
Back Focus		9.43mm	9.39mm
Iris Type		M-Iris	M-Iris
1	2/3*Format	24.18° × 14.6° × 19.42°	17.9°× 10.8°×14.4°
Angle of view ( DXVXH )	1/2*Format	18.18°× 10.97°×14.59°	13.°× 8°×10.5°
( DAVANII )	1/3°Format	13.69° × 8.24° × 10.97°	10°× 5.9°×8°
	1/4"Format	9.15°× 5.5°×7.32°	6.54°× 3.93°×5.23°
Distortion		<-1%	<-1%
Working Dista	nce	0,3m~∞	0.5m~∞
Design Wavele	ength	400~700nm	400~700nm
Filter Thread	183	M30.5 × 0.5	M30.5 × 0.5
Dimension		¢ 32,5 × 33,39mm	¢ 32.9 × 36.91mm
Weight		60g	90g



Item N	lo	AZURE-5020MM	AZURE-7524MM
Resolution		100lp/mm (2MP)	100lp/mm (2MP)
Format		2/3"	2/3"
Mount		C	С
Focal Length		50mm	75mm
F/No		F2.0~F16	F2.4~F22
Back Focus		9.38mm	16.25mm
Iris Type		M-Iris	M-Iris
Indiana.	2/3°Format	12.7°× 7.7°×10.2°	8.32°× 5.02°× 6.7°
Angle of view ( DXVXH )	1/2*Format	9.3°× 5.6°×7,46"	6,2°× 3.7°× 4.5°
( DVAVII )	1/3°Format	7"× 4.2"×5,6"	4.58° × 2.75° × 3.67°
	1/4*Format	4.58°× 2.75°×3,67°	3.05°× 1.83°× 2.44°
Distortion		<0.4%	<0.8%
Working Dista	nce	1m~∞	1m~∞
Design Wavele	ength	400~700nm	400~700nm
Filter Thread		M30.5 × 0.5	M34 × 0.5
Dimension		4 32.9 × 33.65mm	¢ 36× 54.9mm
Weight		80g	140g





Item No		AZURE-0814W3W	AZURE-0918M3M	AZURE-1218M3M
Resolution	- [	120lp/mm (3MP)	120lp/mm (3MP)	120lp/mm (3MP)
Format		2/3*	2/3*	2/3*
Mount		C	С	С
Focal Length		8mm	9mm	12mm
F/No		F1.4-F16	F1.8~F16	F1.8~F16
Back Focus		12.56mm	10.87mm	11.72mm
Iris Type		M-Iris	M-Iris	M-Iris
100000000	2/3"Format	64.26° × 41.66° × 53.76°	61.85°× 39.54°×51.22°	47.7°× 29.8°× 39°
Angle of view (DXVXH)	1/2*Format	53.13°× 33.4°×43,6°	47.09°×29.3°× 38.44°	36.87°× 22.62°×29.86°
( DVAVIII)	1/3"Format	41.11° = 25.36" ×33.4"	36.19° × 22.19° × 29.3°	28.07°× 17.06°×22.62°
Distortion		<0.7%	<-0.5%	<+0.3%
Working Dista	nce	0.1m~∞	0.1m~∞	0.1m-∞
Design Wavele	ength	400~700nm	400~700nm	400~700nm
Filter Thread		M37 × 0.5	M27× 0.5	M27 × 0.5
Dimension		¢ 39× 46.1mm	¢ 29 × 31.7mm	¢ 29 × 41.98mm
Weight		220g	63g	73g



Item N	lo	AZURE-1618M3M	AZURE-2518M3M
Resolution		120lp/mm (3MP)	120lp/mm (3MP)
Format		2/3"	2/3"
Mount	-	С	С
Focal Length		16mm	25mm
F/No		F1.8~F16	F1.8~F16
Back Focus		13.5mm	12.7mm
Iris Type		M-Iris	M-Iris
1 . 1 . 2	2/3°Format	36.8°× 22.5°×29.8°	23.3°× 14,2°×18.8°
Angle of view ( DXVXH )	1/2"Format	28.07°× 17.06°×22.62°	18.18°× 10.97°×14.59°
( DYAYH )	1/3"Format	21,24°× 12.84°×17.06°	13.69°× 8.24°×10.97°
Distortion		<-0.35%	<-0.1%
Working Dista	nce	0.1m~∞	0.15m~∞
Design Wavele	ength	400~700nm	400~700nm
Filter Thread		M27 × 0.5	M27 × 0.5
Dimension		¢ 29× 41.47mm	4 29× 35.03mm
Weight		71g	60.5g



Item N	lo	AZURE-3518M3M	AZURE-5018M3M
Resolution		120lp/mm (3MP)	120lp/mm (3MP)
Format		2/3*	2/3"
Mount		c	c
Focal Length		35mm	50mm
F/No		F1.8~F16	F1.8~F16
Back Focus		11.73mm	11.35mm
Iris Type		M-Iris	M-Iris
4	2/3"Format	16.04°× 9.6°×12.8°	11.52°× 6.86°×9.14°
Angle of view ( DXVXH )	1/2*Format	11.7°× 7°×9,3°	8.4°× 5°×6.6°
(DXVXH)	1/3"Format	9°× 5.3°×7°	6.2°× 3.7°×5°
Distortion		<-0.1%	<-0.1%
Working Dista	nce	0.25m~∞	0.5m~∞
Design Wavele	ength	400~700nm	400~700nm
Filter Thread		M27 × 0.5	M27 × 0.5
Dimension		¢ 29× 38.2mm	¢ 29× 36.4mm
Weight		71g	60g



1/2" ,2/3" Format Manual Iris Fixed Lenses




Item No		AZURE-0414M5M	AZURE-0614M5M	AZURE-0814M5M
Resolution		150(p/mm (5MP)	150lp/mm (5MP)	150lp/mm (5MP)
Format		1/2*	1/2*	2/3"
Mount		C	C	C
Focal Length		4mm	6mm	8mm
F/No		F1.4~F32	F1,4~F16	F1.4~F16
Back Focus		10,34mm	9.8mm	9.91mm
Iris Type		M-Iris	M-Iris	M-Iris
and a beauty of	1/2"Format	85°× 58.76°×75.12°	64.48° × 41.6°×53.8°	66.2"× 42.78"×55.24"
Angle of view (DXVXH)	1/3'Format	73.74°× 48.46°×61.93°	53.13°× 33.39°×43.6°	53.13"× 33.4"×43.6"
( DVAVII )	1/4°Format	53.13°× 33.4°×43.6°	36.87°× 22.6°×29.86°	41.11°× 25.36°×33.4°
Distortion		<-1.5%	<-1%	<-1%
Working Dista	nce	0.1m~∞	0.1m~∞	0.1m - ∞
Design Wavele	ength	400~700nm	400~700nm	400~700nm
Filter Thread		M52 ≈ 0.75	M35.5× 0.5	M35.5 ≈ 0.5
Dimension		¢ 54 × 50,87mm	¢ 38.5 × 50.4mm	¢ 38.5 × 50.7mm
Weight		142g	140g	156g




Item N	o	AZURE-1214M5M	AZURE-1614M5M
Resolution		150lp/mm (5MP)	150lp/mm (5MP)
Format		2/3*	2/3*
Mount		c	c
Focal Length		12mm	16mm
F/No		F1.4~F22	F1.4~F22
Back Focus		10.37mm	10.27mm
Iris Type		M-Iris	M-Iris
	2/3"Format	47.1°× 29.44°×39.58°	36.6°× 22.6°×29.78°
Angle of view ( DXVXH )	1/2"Format	36.86°× 22.62°×29.86°	28.07°× 17.06°×22.62°
(DXVXII)	1/3"Format	28.07°× 17.06°×22.62°	21.23°× 12.84°×17.06°
Distortion		<-0.3%	<-0,3%
Working Dista	nce	0.1m ~ ∞	0.1m ~ ∞
Design Wavele	ength	400~700nm	400~700nm
Filter Thread		M35.5 × 0.5	M35.5 × 0.5
Dimension		¢ 38.5 × 46.03mm	¢ 38.5 × 46.03mm
Weight		150g	139g









Item N	lo	AZURE-2514M5M	AZURE-3514M5M
Resolution		150lp/mm (5MP)	150lp/mm (5MP)
Format		2/3*	2/3*
Mount		С	C
Focal Length		25mm	35mm
F/No		9.98mm	13.09mm
Back Focus		F1.4~F16	F1.4~F16
Iris Type		M-Iris	M-Iris
4.50000000	2/3"Format	23.6°×14.32"×19.06°	17.4°× 10.6°×14°
Angle of view ( DXVXH )	1/2"Format	18.18°× 10.97°×14.59°	13.04°× 7.85°×10.45°
( DAVAN )	1/3"Format	13.69°× 8.24°×10.97°	9.8°× 5.89°×7.85°
Distortion		<-0.1%	<-0.05%
Working Dista	nce	0.2m ~ ∞	0.35m~∞
Design Wavele	ength	400~700nm	400-700nm
Filter Thread		M35,5 × 0.5	M35.5 × 0.5
Dimension		¢ 38.5 × 34.61mm	¢ 38.5 × 38mm
Weight		110q	120g





Item N	o	AZURE-5020M5M	AZURE-7520M5M
Resolution		150lp/mm (5MP)	150lp/mm (SMP)
Format		2/3"	2/3*
Mount		C	c
Focal Length		50mm	75mm
F/No		F2.0~F32	F2.0~F22
Back Focus		9.78mm	10.7mm
Iris Type		M-Iris	M-Iris
	2/3"Format	12,36°× 7,45°×9,92°	8,36°× 5.04°× 6.72°
Angle of view ( DXVXH )	1/2"Format	9.04°× 5.42°×7.24°	6.1°× 3.67°×4.89°
( DAVAN )	1/3"Format	6.78°× 4.08°×5.42°	4.58°× 2.75°×3.67°
Distortion		<-0.1%	<-0.1%
Working Dista	nce	0.4m~∞	0.8m~∞
Design Wavele	ength	400~700nm	400~700nm
Filter Thread		M35.5 × 0.5	M40.5 × 0.5
Dimension		¢ 38.5 × 44.94mm	¢ 42 × 69.28mm
Weight		152g	290g



# Product features


- Designed for True Factory Automation
- · Supports up to 1" Sensors
- · Optimized for Close Measuring System
- · Multilayer BBAR coating at 400nm 950nm
- · Feature Locking Iris and Focus Adjustment




Item No		AZURE-NV0820M6M	AZURE-NV1220M6M	
Resolution		170lp/mm (6MP)	170lp/mm (6MP)	
Format		2/3"(compatible with 1/1.2" sensor)	2/3"( compatible with 1/1.2" sensor)	
Mount		C	C	
Focal Length		8mm	12mm	
F/No		F2.0~16	F2.0~16	
Back Focus		12.476mm	11.99mm	
Iris Type		M-Iris	M-Iris	
Angle of view ( DXVXH )	2/3"Format	69°× 44.84°×57.62°	48.22°× 29.92°×39.4°	
	1/2"Format	53.13°× 33.4°×43.6°	36.86°× 22.62"×29.86°	
	1/3"Format	41.11°× 25.36°×33.4°	28.07°× 17.06°×22.62°	
Distortion		<0.45%	<1%	
Working Distance		0.1m ~ ∞	0.1m ~ ∞	
Optimum Working Distance		0.2~0.4m	0.2~0.4m	
Design Wavelength		400~700nm	400~700nm	
Filter Thread		M58 × 0.75	M37.5 × 0.5	
Dimension		¢ 61 × 59.34mm	¢40×47.76mm	
Weight		110.8g		
100				









Item No		AZURE-NV1620M6M	AZURE-NV2520M6M	
Resolution		170lp/mm (6MP)	170lp/mm (6MP)	
Format		2/3"( compatible with 1/1.2" sensor )	2/3"(compatible with 1" sensor)	
Mount		С	С	
Focal Length		16mm	25mm	
F/No		F2.0~16	F2.0~16	
Back Focus		12.88mm	13.029mm	
Iris Type		M-Iris	M-Iris	
Angle of view ( DXVXH )	2/3*Format	36.7°× 22.3°×29.6°	22.6°×13.6°×18°	
	1/2°Format	28.07°× 17.06°×22.62°	18.18°× 10.97°×14.59°	
	1/3"Format	21.23°× 12.84°×17.06°	13.68°× 8.24°×10.97°	
Distortion		<0.5%	<-0.25%	
Working Distance		0.1m ~ ∞	0.2m ~ ∞	
Optimum Working Distance		0.2~0.4m	0.2~0.4m	
Design Wavelength		400~700nm	400~700nm	
Filter Thread		M30.5* 0.5	M30.5 × 0.5	
Dimension		¢ 38 × 53.05mm	¢ 38 × 40.17mm	
Weight		106.1g	97.3g	










Item No		AZURE-NV3520M6M	AZURE-NV5020M6M	
Resolution		170lp/mm (6MP)	170lp/mm (6MP)	
Format		2/3*(compatible with 1* sensor)	2/3"( compatible with 1" sensor )	
Mount		C	c	
Focal Length		35mm	50mm	
F/No		F2,0~16	F2.0~16	
Back Focus		10.52mm	7.26mm	
Iris Type		M-Iris	M-Iris	
Angle of view ( DXVXH )	2/3°Format	17°× 10°×13.3°	10.14°× 6.14°×8.16°	
	1/2"Format	13.04°× 7.85°×10.45°	8.32° × 5.0° × 6.86°	
	1/3"Format	9.8"× 5.89"×7.85"	6.24° × 3.74° × 5.0°	
Distortion		<-0.35%	<0.05%	
Working Distance		0.2m - ∞	0.2m ~ ∞	
Optimum Working Distance		0.2~0.4m	0.2~0.4m	
Design Wavelength		400~700nm	400~700nm	
Filter Thread		M30,5 × 0.5	M37.5 × 0.5	
Dimension		¢ 38 × 38.74mm	¢ 43.2 × 62.74mm	
Weight		94.4g	C. P	











Item No		AZURE-0518M10M	AZURE-0818M10M	AZURE-1218M10M
Resolution	- 1	200lp/mm (10MP)	200lp/mm (10MP)	200lp/mm (10MP)
Format		2/3*	2/3*	2/3"
Mount		ć	c	Ċ
Focal Length		5mm	8mm	12mm
F/No		F1.8~F11	F1.8~F22	F1.8~F32
Back Focus		8.54mm	12.47mm	16.22mm
Iris Type		M-Iris	M-Iris	M-Iris
Angle of view (DXVXH)	2/3"Format	96.54"× 67.6°×84°	65.64°× 42.7°×55.6°	48.9°× 30.6°×40.1°
	1/2"Format	77.31°× 51.28°×65.24°	53.13"× 33.4"×43.6"	36.8°× 22.5°×29.7°
	1/3"Format	61.93°× 39.6°×51.28°	41.11°× 25.36°×33.4°	28°× 17°×22.5°
	1/4"Format	43.6°× 27°×35.49°	28.07°× 17.06°×22.62°	18.92°× 11.42×15.19°
Distortion		<-4.2%	<-1%	<-0.42%
Working Distance		0.1m ~ ∞	0.1m ~ ∞	0.1m ~ ∞
Design Wavelength		400~700nm	400~700nm	400~700nm
Filter Thread		M62 × 0.75	M37.5 × 0.5	M27× 0.5
Dimension		¢ 65 × 43mm	¢40 × 53,76mm	¢ 39× 47.83mm
Weight		150g	180g	140g