




# Piccolo PCIe

PCIe video capture card with BNC and S-Video connectors for standard PAL/NTSC cameras



## At a Glance

- BNC, DB9 and S-Video connectors
- PCIe x1 bus
- Acquisition of composite or separate video (S-Video) signals
- One video decoder, 25/30 images per second (50/60 fields per second)
- PCI and PCIe versions available

## Benefits

Robust, reliable, dependable video capture card

Take advantage of the lowest-cost industrial cameras available on the market

Supports S-Video signals for the highest quality color images

Windows drivers available

## Applications

### Machine Vision for the General Manufacturing Industries

- Low cost image acquisition from industrial analog cameras for inspection machines

### Life Sciences & Medical

- Standard and high-definition image acquisition for endoscopy applications
- Standard and high-definition image acquisition for dental applications

### Microscopy

- High-definition image acquisition for offline inspection stations
- High-definition image acquisition for laboratory and measuring microscopes

## Specifications

### Mechanical

Form Factor	PCI Express card
Format	Low profile, half length, 1-lane PCI Express card
Dimensions	L 115.00 mm x H 64.40 mm

## Host bus

Standard	PCI Express 1.0
Link width	1 lane
Link speed	2.5 GT/s (PCIe 1.0)
DMA	32-bit
Peak delivery bandwidth	256 MB/s
Power consumption	Max. 2.6 W (200 mA @ +3.3V, 160 mA @ +12V), excluding I/O power output

## Camera / video inputs

Interface standard(s)	NTSC-M, PAL-B/G, RS-170, CCIR
Connectors	<ul style="list-style-type: none"><li>• VIDEO 1: BNC female connector on the bracket for composite video input</li><li>• S-VIDEO: 4-pin mini-DIN female connector on the bracket for components video input</li><li>• DB9: 9-pin sub-D female connector on the bracket (not available with low-profile bracket)</li><li>• Internal: 10-pin shrouded male header on the PCB</li></ul>
Termination resistor	Selectable using jumpers on the PCB
Native resolution	Square pixels, broadcast and custom resolutions
Frame rate	Up to 25/30 images per second, 50/60 fields per second
Number of cameras	3
Number of cameras (at full frame rate)	1
Line-scan cameras supported	No

## Video delivery

Raw video format(s)	Planar, packed, YUV and RGB color formats
Deliverable video resolution (SD)	Frame, field, CIF, QCIF and custom image formats

## General Purpose Inputs and Outputs

Number of lines	4 I/O lines (IO)
Connectors	<ul style="list-style-type: none"><li>• DB9: 9-pin female sub-D connector on the bracket (not available when the low-profile bracket is installed)</li><li>• INTERNAL: 10-pin dual-row 0.1" shrouded header on the PCB</li></ul>
Usage	General purpose IO
Electrical specifications	IO: TTL-compatible I/O lines

## Software

Host PC Operating System	<ul style="list-style-type: none"><li>• Microsoft Windows 10, 8.1, 7 for x86 (32-bit) and x86-64 (64-bit) processor architectures</li><li>• Linux for x86 (32-bit) and x86-64 (64-bit) processor architectures</li></ul> Refer to release notes for details
APIs	<ul style="list-style-type: none"><li>• MultiCam 32- and 64-bit binary libraries (Windows and Linux), for ISO-compliant C/C++ compilers</li><li>• DirectShow 32- and 64-bit filters (Windows only), for Microsoft Visual C++ compilers</li></ul>

## Environmental conditions

Operating ambient air temperature	0 to +50 °C / +32 to +122 °F
Operating ambient air humidity	10 to 90% RH non-condensing
Storage ambient air temperature	-20 to +70 °C / -4 to +158 °F
Storage ambient air humidity	10 to 90% RH non-condensing

## Certifications

---

Electromagnetic - EMC standards	<ul style="list-style-type: none"><li>• European Council EMC Directive 2004/108/EC</li><li>• United States FCC rule 47 CFR 15</li></ul>
EMC - Emission	<ul style="list-style-type: none"><li>• EN 55022:2010 Class B</li><li>• FCC 47 Part 15 Class B</li></ul>
EMC - Immunity	<ul style="list-style-type: none"><li>• EN 55024:2010 Class B</li><li>• EN 61000-4-2</li><li>• EN 61000-4-3</li><li>• EN 61000-4-4</li><li>• EN 61000-4-5</li><li>• EN 61000-4-6</li></ul>
KC Certification	Korean Radio Waves Act, Article 58-2, Clause 3
Flammability	PCB compliant with UL 94 V-0
RoHS	European Union Directive 2011/65/EU (ROHS2)
REACH	European Union Regulation 1907/2006
WEEE	Must be disposed of separately from normal household waste and must be recycled according to local regulations

---

## Ordering Information

---

Product code - Description	<ul style="list-style-type: none"><li>• 1685 - Picolo PCIe</li></ul>
----------------------------	--

---



## AMERICA

### **Euresys Inc.**

27126-B Paseo Espada - Suite 704  
San Juan Capistrano, CA 92675 - United States

Phone: +1 949 743 0612

Email: [sales.americas@euresys.com](mailto:sales.americas@euresys.com)

## EMEA

### **Euresys SA**

Liège Science Park - Avenue du Pré Aily, 14  
4031 Angleur - Belgium

Phone: +32 4 367 72 88

Email: [sales.europe@euresys.com](mailto:sales.europe@euresys.com)

## EMEA

### **Sensor to Image GmbH**

Lechtorstrasse 20 -  
86956 Schongau - Germany

Phone: +49 8861 2369 0

Email: [sales.europe@euresys.com](mailto:sales.europe@euresys.com)

## ASIA

### **Euresys Pte. Ltd.**

750A Chai Chee Road - #07-15 Viva Business Park  
Singapore 469001 - Singapore

Phone: +65 6445 4800

Email: [sales.asia@euresys.com](mailto:sales.asia@euresys.com)

## CHINA

### **Euresys Shanghai Liaison Office**

Unit 802, Tower B, Greenland The Center - No.500 Yunjin Road, Xuhui District  
200232 Shanghai - China

Euresys上海联络处

上海市徐汇区云锦路500号绿地汇中心B座802室  
200232

Phone: +86 21 33686220

Email: [sales.china@euresys.com](mailto:sales.china@euresys.com)

## JAPAN

### **Euresys Japan K.K.**

Expert Office Shinyokohama - Nisso Dai 18 Building, Shinyokohama 3-7-18  
Kouhoku-Ku, Yokohama-Shi 222-0033 - Japan

〒222-0033

神奈川県横浜市港北区新横浜3-7-18 日総第18ビル エキスパートオフィス新横浜

Phone: +81 45 594 7259

Email: [sales.japan@euresys.com](mailto:sales.japan@euresys.com)

More at [www.euresys.com](http://www.euresys.com)

