



福建福特科光电股份有限公司

Foctek Photonics, Inc.

镜头参数 (Parameter of Lens)

型号 (Model) :

CS-M2. 5IR(8MP)-F



分辨率 (Resolution)	8 Megapixel			
像面尺寸 (Image Circle)	Φ6.4 mm			
焦距 (Focal length)	2.5mm			
通光孔径 (Aperture)	F1.6			
接口 (Mount)	CS			
视场角 (Field Angle) (°)		2/3"	1/2"	1/2.7"
	D	190	190	190
	H	190	190	134
	V	190	117.4	94
畸变 (Optical Distortion)	-97.90%			
最近物距 (M. O. D.)	0.3m			
外形尺寸 (Dimension)	Φ37×48.94mm			
重量 (Weight)	80.4±2g			
法兰后焦距 (FMBF)	12.526mm			
光学后焦距 (BFL)	5.99mm			
机械后焦距 (MBF)	5.85mm			
日夜共焦 (IR Correction)	Yes			
操作方法 (Operation)	光圈 (Iris)	手动光圈 (Manual)		
	聚焦 (Focus)	手动聚焦 (Manual)		
	变焦 (Zoom)	/		
工作温度 (Operating temperature)	-20℃~+60℃			

尺寸 (Size)

尺寸公差 (size tolerance) (mm) :	0-10±0.05	10-30±0.10	30-120±0.20
角度公差 (angle tolerance)	±2°		



福建福特科光电股份有限公司

Foctek Photonics, Inc.

## 检测标准 (Test Standard)

型号 (Model):

CS-M2.5IR(8MP)-F

检测项目 Test Items

检测内容 Test Content

1	逆投影检测 Resolution Test	Test Range	$\Phi 4$ (diameter 0.6m)
		Center $\geq$	300 lp/mm
		edge $\geq$	200 lp/mm
		Image standard	The image should be clear.
	环境 Environment	25 $\pm$ 2 $^{\circ}$ C, $\leq$ 1 lux Dark room	

2	外观检测 Appearance Inspection	Appearance (Inner barrel)	60-40: The maximum scratch width is allowed to be 0.06mm, the length allows the 1/4 edge position of the lens; the visually invisible fineness is negligible; the maximum diameter of the pip is allowed to be 0.2mm, and only one lens surface is allowed; the pip is smaller than 0.002mm $\sim$ 0.005m can be neglected; the film color is uniform; there is no obvious color spot on the surface.
		Appearance (Outer barrel)	The lens barrel has no obvious color difference, scratch, break, deformation; the glue is not allowed to overflow into the effective light path; no word drop, clear writing, the same font size, even spacing, etc.
		Rotation	Feel the rotation back and forth smoothly without jumping, stuck and abnormal sounds, etc
	环境 Environment	25 $\pm$ 2 $^{\circ}$ C 700 $\sim$ 1000 lux	



福建福特科光电股份有限公司

Foctek Photonics, Inc.

环境可靠性测试 (Reliability and Environmental Testing)

型号 (Model):

CS-M2.5IR(8MP)-F

检测项目 Test Items

检测内容 Test Content

1

温度循环试验  
Temperature Cycling Test

镜头在试验温度  $(-30 \pm 3)^\circ\text{C}$  放置1.5小时,  $(70 \pm 3)^\circ\text{C}$  放置3小时  
的条件下, 放置2个循环。试验后, 将镜头放置于室温 24小时后进行  
检验, 各指标均合格。

Lens is placed on two cycles in the test temperature  $(-30 \pm 3)^\circ\text{C}$  for 1.5 hours and in  $(70 \pm 3)^\circ\text{C}$  for 3 hours separately. Then, the indicators are qualified after placing the lens at room temperature for 24 hours.

2

高温高湿试验  
Damp heat test

镜头在试验温度  $(70 \pm 3)^\circ\text{C}$ , 湿度85%RH的条件下, 放置48小时。  
试验后, 将镜头放置于室温 24小时后进行检验, 各指标均合格。

Lens is placed in the test temperature  $(70 \pm 3)^\circ\text{C}$ , humidity 85% RH for 48 hours. Then, the indicators are qualified after placing the lens at room temperature for 24 hours.

3

跌落试验  
Drop Test

镜头在1米高  $(\pm 0.1\text{米})$  处, 自由跌落到混凝土地板上。  
试验后, 镜头各指标均合格。

Lens drops from the height of  $(1 \pm 0.1\text{m})$  to the concrete ground. After the testing, the indicators are qualified.

4

振动试验  
Vibration Test

镜头正弦波振动2小时, 在振幅为1mm, 频率为50Hz的条件下, 试验  
后, 镜头各指标均合格。

Lens vibrates 2h in sinusoidal wave under 1 mm of amplitude and 50Hz of frequency. After the testing, the indicators are qualified.



福建福特科光电股份有限公司

Foctek Photonics, Inc.

包装规格 (Packing Specification)

型号 (Model) :

CS-M2. 5IR (8MP)-F

1. Stick label on the surface of lens after capped.
2. Put the lens into the carton box.
3. The unit will be packaged in a corrugated box.
4. Seal the corrugated box with tape and mark the surface.

