

## DV4x12.5SR4A-1



High image-quality monitoring with optical performance supporting 5 megapixels. Advanced design engineering and special optic glass adopted, best suited for color, Black & White, and Day and Night cameras. f12.5-50mm, 4x zooming application compatible lens. Designed to maximize optical performance with high-accuracy aspheric lens, low-dispersion glass, and high refractive-index glass. Built-in ND filter of T360, supporting high sensitivity cameras.

Specifications [Features](#)

<b>Mount</b>	C		
<b>Focal length</b>	12.5 mm - 50 mm (4x)		
<b>Focus</b>	Manual		
<b>Iris Range</b>	F1.6 - T360 (Equivalent to F360)		
<b>Iris</b>	Manual		
<b>Zoom</b>	Manual		
<b>Angular Field of View 4 : 3 Aspect Ratio</b>	1/1.8"	<b>Wide</b>	32°54' × 24°37'
		<b>Tele</b>	8°14' × 6°13'
	1/2"	<b>Wide</b>	29°32' × 22°7'
		<b>Tele</b>	7°26' × 5°36'
	1/3"	<b>Wide</b>	22°7' × 16°34'
		<b>Tele</b>	5°36' × 4°12'
<b>Angular Field of View 16 : 9 Aspect Ratio</b>	1/1.8"	<b>Wide</b>	35°52' × 20°6'
		<b>Tele</b>	8°57' × 5°5'
	1/2"	<b>Wide</b>	32°12' × 18°3'
		<b>Tele</b>	8°4' × 4°35'
	1/3"	<b>Wide</b>	24°6' × 13°32'
		<b>Tele</b>	6°5' × 3°27'
<b>Focusing Range (From Front of the Lens)</b>	∞ - 0.8 m		
<b>Filter Thread</b>	-		
<b>Mass</b>	170 g		
<b>Coil Resistance</b>	<b>Drive Coil</b>	-	
	<b>Damping Coil</b>	-	
<b>Current Consumption</b>	-		

**Note**

\* With Metal Mount