



| | | | | |
|---|------------|-----------------|------------|-----------------|
| 1.1" 1.8/35mm C | | 1.1" | 1" | 2/3" |
| FOCAL LENGTH | | f=35mm | | |
| F-NUMBER | | F=1.8-16 | | |
| PICTURE SIZE | | 10.6×14.1mm | 9.6×12.8mm | 6.6×8.8mm |
| ANGLE OF VIEW (∞) | VER. ANGLE | 16.7° | 15.2° | 10.5° |
| | HOR. ANGLE | 22.1° | 20.2° | 14.0° |
| | DIA. ANGLE | 27.5° | 25.1° | 17.4° |
| DISTORTION (TV) | | 0.01% | 0.01% | 0.01% |
| FIELD OF VIEW (MINIMUM FOCUS DISTANCE) | VER. | 63mm | 57mm | 39mm |
| | HOR. | 84mm | 76mm | 52mm |
| | DIA. | 104mm | 95mm | 65mm |
| MINIMUM FOCUS DISTANCE | | 0.2m | | |
| FLANGE BACK | | 17.526mm in air | | |
| BACK FOCUS | | 15.5mm in air | | |
| FILTER SCREW SIZE | | M40.5×0.5 | | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT φ33.4mm | | REAR φ16.2mm |
| MOUNT | | C-MOUNT | | |
| EXIT PUPIL | | -40.0mm | | |
| TEMPERATURE RANGE | | -10~+50°C | | |
| STORAGE TEMPERATURE RANGE | | -20~+60°C | | |
| RESOLUTION CENTER/CORNER | | CENTER 200lp/mm | | CORNER 100lp/mm |
| WEIGHT | | 205g | | |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | | |
|------------|--------|-----|------------------|------|--------|
| | | 尺度 | 1/1 | 工場番号 | LM35FC |
| | | 機種名 | 1.1" F1.8 f=35mm | | |
| 2019.12.02 | 表記誤記修正 | 機種番 | LM35FC24M 外観図 | | |
| 2018.02.09 | 印字誤記修正 | | | | |
| 2017.09.15 | 作成年月日 | | | | |