



| φ23 2.0/35mm C | | |
|---------------------------|------------|------------------------------|
| FOCAL LENGTH | | f=35mm |
| MAX. DIAMETER (RATIO) | | F=1:2.0~16 |
| ELEMENT | | 6 GROUPS 8 ELEMENTS |
| PICTURE SIZE | | 13.8×18.4mm |
| ANGLE | VER. ANGLE | 22.4° |
| | HOR. ANGLE | 29.6° |
| | DIA. ANGLE | 36.6° |
| DISTORTION (TV) | | -0.17% |
| SHOOTING RANGE AT | VER. | 75mm |
| MINIMUM FOCUS | HOR. | 100mm |
| DISTANCE | DIA. | 125mm |
| MINIMUM FOCUS DISTANCE | | 0.2m |
| FLANGE BACK | | 17.526mm in air |
| BACK FOCUS | | 15.2mm in air |
| FILTER SCREW SIZE | | M37.5×0.5 |
| FRONT/REAR EFFECTIVE DIA. | | FRONT φ26.5mm REAR φ16.9mm |
| MOUNT | | C-MOUNT |
| EXIT PUPIL | | -26.6mm |
| TEMPERATURE RANGE | | -10~+50°C |
| STORAGE TEMPERATURE RANGE | | -20~+60°C |
| RESOLUTION CENTER/CORNER | | CENTER 160本/mm CORNER 80本/mm |
| LENS COATING | | WIDE BAND MULTI COATING |
| WEIGHT | | 210 g |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | |
|------------|-------|---------------------|-------|-----------|
| | | 尺度 1/1 | 承認 八木 | 製 富永 図 |
| | | 機種名 φ23 F2.0 f=35mm | | |
| | | 機種番 LM35XC | | |
| 2010.06.01 | 作成年月日 | | | |