



φ16 2.0/50mm C		
FOCAL LENGTH		f=50mm
MAX. DIAMETER (RATIO)		F=1:2.0~22
ELEMENT		6 GROUPS 7 ELEMENTS
PICTURE SIZE		12.8x9.6mm
ANGLE	VER. ANGLE	11.0°
	HOR. ANGLE	14.6°
	DIA. ANGLE	18.0°
DISTORTION (TV)		0.3%
SHOOTING RANGE AT	VER.	52mm
MINIMUM FOCUS	HOR.	70mm
DISTANCE	DIA.	87mm
MINIMUM FOCUS DISTANCE		0.3m
FLANGE BACK		17.526mm in air
BACK FOCUS		21.6mm in air
FILTER SCREW SIZE		M34x0.5
FRONT/REAR EFFECTIVE DIA.		FRONT φ27mm REAR φ16mm
MOUNT		C-MOUNT
EXIT PUPIL		-19.1mm
TEMPERATURE RANGE		-10~+50° C
STORAGE TEMPERATURE RANGE		-20~+60° C
RESOLUTION CENTER/CORNER		CENTER 160L/mm CORNER 120L/mm
LENS COATING		WIDE BAND MULTI COATING
WEIGHT		g

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺 度	1/1	承 認	八木	製 図	大口
		LM50SC					
		1" F2.0 f=50mm					
2013.05.10	作成年月日						