

MV-CE060-10UM/UC 6MP, 1/1.8" CMOS, USB 3.0 Camera



The Hikvision MV-CA060-10UM/UC 6 MP 1/1.8" CMOS USB 3.0 Camera is a high quality device that can be used in a variety of applications, including electronic semiconductor fabrication, factory automation, quality inspection.


Key Features

- Supports auto exposure control, LUT and gamma correction.
- Cameras can be synchronized with hard trigger and soft trigger.
- Compact structure, 29mm×29mm×30mm, suitable for smaller installation requirements.
- The USB3.0 interface is tightly locked to prevent accidental unplugging and dropping.
- Compatible with USB 3.0 Vision V1.0, can be supported by third party software.


Application Scenarios

- Electronic semiconductor
- Factory automation
- Quality Inspection

Spectral Response



MV-CE060-10UM Quantum Efficiency



MV-CE060-10UC Quantum Efficiency

Order Models

Mono: MV-CE060-10UM

Color: MV-CE060-10UC



Specifications

Model	MV-CE060-10UM	MV-CE060-10UC
Parameters	6MP, 1/1.8" CMOS, USB 3.0 Camera	
Camera		
Sensor	IMX178	
Pixel Size	2.4μm×2.4μm	
Sensor Size	1/1.8"	
Resolution	3072x2048	
Frame Rate	42.7fps	
Dynamic Range	>65dB	
SNR	>40dB	
Gain Range	0-20dB	
Exposure Time	24μs-1sec	
Shutter Mode	Rolling shutter, with GlobalReset supported. Auto-exposure, Manual exposure, and One-key exposure	
Data Interface	USB 3.0	
General Purpose I/O	Opto-isolated input x1, Opto-isolated output x1, Bi-directional non-isolated I/O x1	
Buffer	128MB	
Data Format	Mono 8/10/10p/12/12p	Mono 8/10/12, Bayer RG 8/10/10p/12/12p, YUV 422 Packed, YUV 422_YUYV_Packed, RGB8
General		
Power	Approx. 2.7W@12VDC, Voltage 5~15VDC, USB 3.0 power supply supported	
Temperature	Working Temperature 0~50°C, Storage Temperature -30~70°C	
Humidity	20%-85% RH Without Condensation	
Dimension	29mm×29mm×30mm	
Weight	Approx. 56g	
Lens Interface	C-Mount	
Software	MVS or Third-Party Software supporting USB 3.0 Vision Protocol	
Operating System	Windows XP/7/10 32/64bits	
Compliance	USB 3.0 Vision	
Certification	CE, FCC, RoHS	

Recommended Accessories

- **Power:** 12VDC @1A power switch or adapter
- **Cable:** Micro USB 3.0 cable (B Type) recommended

Distributed by RMA Electronics, Inc.



www.rmaelectronics.com

Dimensions

